

DATASHEET RF CABLE ASSEMBLY

MEC-RFCA-SMA(MRA)-BNC(M)-0.4Meter





END 1: SMA MALE RIGHT ANGLE

END 2: BNC MALE STRAIGHT

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

Electrical Specifications

Frequency (GHz)	DC-1 GHz	PROPRIETARY NOTE THIS DOCUMENT CONTAINS THE CONFIDENTIAL INFORMATION AND PROPRIETARY TO MEC ELECTRONICS & COMMUNICATION PVT LTD. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN OBTAINED WRITTEN CONSENT FROM MEC.		<small>MEC Electronics and Communication Pvt Ltd RF Products Connectors, Cable Assemblies, Adaptors & Customization E-mail: info@mec.org.pk Website: www.mec.org.pk</small>
Characteristic Impedance (Ω)	50 Ω	DESC: SMA Male Right Angle to BNC Male Straight RF Cable Assembly		
Insertion Loss (dB)	≤ 1	P/N: MEC-RFCA-SMA(MRA)-BNC(M)-0.4Meter		
		⊕ 	<small>** MRA : MALE RIGHT ANGLE ** MS : MALE STRAIGHT</small>	SHEET 1 OF 1